

# Soliflex CB TPU/30 I. blue 1200mm FG 2 rows

Article code: SFPU000817

## General information

<b>Product group</b>	Soliflex		
<b>Main product feature</b>	Positive drive, Chemical resistant, Non-stick, Wear resistant		

## Belt construction

<b>Material</b>	TPU-E		
<b>Top side</b>	<b>finish</b>	smooth	
<b>Bottom side</b>	<b>finish</b>	matt	
<b>Color</b>	Light blue		

## Characteristics

<b>Food Grade (FG)</b>	yes	According to: EU 1935/2004, EU 10/2011; FDA; no
------------------------	-----	---

## Technical data

<b>Pitch</b>			39.7 mm	1.56 in.
<b>Hardness</b>	according to ISO 868		98A Shore	
<b>Belt thickness</b>			3 mm	0.12 in.
<b>Weight</b>			4.6 kg/m <sup>2</sup>	0.94 lbs/ft <sup>2</sup>
<b>Force at 1% elongation</b>	according to ISO 21181		2.7 N/mm	15.42 lbs/in.
<b>Operating temperature</b>	continuous	from/to	-10 / 70 °C	14 / 158 °F
<b>Minimum pulley diameter</b>	flexing		124 mm	4.88 in.
	backflexing		250 mm	9.84 in.
<b>Belt width</b>	maximum		1200 mm	47.24 in.
	standard		1200 mm	47.24 in.

## Fabrication

<b>Recommended splice method</b>	Butt weld
----------------------------------	-----------

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.  
 Keep the belt tension to a practical working minimum for maximum belt and machine life.  
 Store loose and wrapped in plastic. The allowable product temperature may vary.

## Soliflex layout

